

1 2 3 4 5 6 7 8

REVISIONS				
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE		

13.8
7
3.5

RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)

11 HEX
19.3
10 SQ.
17.4

1. CRIMPED FERRULE
HEX CRIMP SIZE .178"

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS
2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MN THICK
3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK
OVER COPPER PL. 50 MIN. THICK
4. TEFLON

7	FERRULE	NOTE 1	NOTE 2	1	FR-43-53-30 -42-125
6	COVER	NOTE 1	NOTE 2	1	CV-80-1
5	CONTACT PIN	NOTE 1	NOTE 3	1	3832-1112A1-5
4	SHELL	NOTE 1	NOTE 2	1	3832-1004A4-1
3	INSULATOR	NOTE 4	NATURAL	1	3832-1112A1-3 -75T
2	BODY	NOTE 1	NOTE 2	1	3832-1112A1-2
1	HOUSING	NOTE 1	NOTE 2	1	3832-1112A1-1 -05

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A

DIMENSIONS ARE IN MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

PART NO.
APPROVED
DATE
02-23-'11
CHECKED
DATE
02-23-'11
DRAWN
DATE
02-23-'11

TITLE
F R/A CRIMP PLUG
(FOR RG-179/U, 187A/U)
DRAWING NO.
3832-1112A1-05-75
FILE NO.
R:\D\G\DWG\3832\1112A1\05\75

G.L.I.

1 2 3 4 5 6 7 8